


# PAC-53GH

3-slot Half-size Compact Chassis

- 1 Application Server Platform
- 2 Single Board Computer
- 3 IBX Series POS PC
- 4 AFOLLUX POS Panel PC
- 5 Video Capture Card
- 6 KAMIO RISC
- 7 IOVU Open HMI
- 8 VITO Universal Controller
- 9 DINO BLADE
- 10 LCD Product Series
- 11 Embedded System
- 12 Industrial Computer Chassis
- 13 Power Supply
- 14 Peripherals



HDD is not included in package.



## Features

- ◆ RoHS compliant design
- ◆ Two USB ports on the front panel
- ◆ One 2.5" internal HDD bay


## Specifications

◆ Construction	Heavy duty metal
◆ SBC Form Factor	Half-size, slot CPU cards
◆ Drive Bays	1 x 2.5" HDD
◆ I/O ports	2 x USB
◆ I/O openings	1 x LPT , 1 x COM
◆ Expansion Slots	3 slots
◆ Indicators	Power, HDD
◆ Button	Power switch, reset
◆ Operating Temperature	0°C~50°C
◆ Operation Humidity	10% ~ 90%
◆ Color	W: White
◆ Weight (Net/Gross)	2 kg / 3.8 kg
◆ Dimensions (DxWxH)	218 mm x 95 mm x 200 mm

## Ordering Information

Part No.	Description
PAC-53GHW/ACE-916AP/IP-3S	3-slot half-size chassis, with ACE-916AP-RS and IP-3S-RS-R30, RoHS
PAC-53GHW/ACE-916AP/BP-3S	3-slot half-size chassis, with ACE-916AP-RS and BP-3S-RS-R30, RoHS
PAC-53GHW/ACE-4518AP/IP-3SA	3-slot half-size chassis, with ACE-4518AP-RS and IP-3SA-RS-R40, white, RoHS

## Dimensions



## Backplane Options

Model No.	SBC Type	PCI	ISA	PCIe			PSU Connector
				x1	x4	x16	
BP-3S-RS-R40	ISA	0	3	0	0	0	AT
IP-3S-RS-R40	PCISA	2	0	0	0	0	AT
IP-3SA-RS-R40	PCISA	2	0	0	0	0	ATX

## Power Supply Options

Type	Model No.	Watt
AT	ACE-916AP-RS	150W
ATX	ACE-4518AP-RS	180W

PAC-53GH can support single 1U height PSU. For more models of IEI PSU, please visit [www.ieiworld.com](http://www.ieiworld.com)