



RACK-1151G

1U 3-slot Full-size Rackmount Chassis



CD-ROM and HDD are not included in package.



* RACK-1151G supports add-on cards up to 150 mm in length

Features

- ◆ RoHS compliant design
- ◆ Two USB ports on the front panel
- ◆ One 5.25" drive bay
- ◆ One 3.5" internal hard drive bay
- ◆ Three, 4 cm cooling fans
- ◆ LCD message module on the front panel

Specifications


◆ Construction	Heavy duty metal
◆ SBC Form Factor	Full-size, slot CPU card
◆ Drive Bays	1 x 5.25" 1 x 3.5" HDD (internal)
◆ Cooling Fans	3 x 4 cm
◆ I/O Ports	2 x USB
◆ I/O openings	1 x COM, 1 x LPT
◆ Expansion Slots	3 slots
◆ Indicators	Power, HDD
◆ Buttons	Power switch, reset button
◆ LCD module	16x2 programmable LCD message module (LCM-02G)
◆ Operating Temperature	0°C~50°C
◆ Operation Humidity	10% ~ 90%
◆ Color	B: Black
◆ Weight (Net/Gross)	7 kg / 9 kg
◆ Dimensions (DxWxH)	440 mm x 431 mm x 44 mm

RACK-1150G and RACK-1151G can support processors with a maximum TDP of 31 W.

Ordering Information

Part No.	Description
RACK-1151GB/ACE-4518AP/PCI-2SD2	1U 3-slot full size rackmount chassis, black, with ACE-4518AP-RS and PCI-2SD2-RS-R40, RoHS

Dimensions



Backplane Options

Model No.	SBC Interface	PCI	ISA	PSU Connector
PCI-2SD2-RS-R40	PICMG 1.0	2	0	ATX

Adapting cable 32100-040600-RS is required when connecting PCI-2SD2-RS-R40 to a standard ATX supply.

Power Supply Options

Type	Model No.	Watt
ATX	ACE-4518AP-RS	180W
	ACE-4525AP-RS	250W
	ACE-4520C-RS	200W

RACK-1151G can support single 1U height PSU, for more models of IEI PSU, please visit www.ieiworld.com

1
Application
Server
Platform

2
Single
Board
Computer

3
IBX Series
POS PC

4
AFOLUX
POS
Panel PC

5
Video
Capture
Card

6
KAMIO
RISC

7
IOVU
Open HMI

8
VITO
Universal
Controller

9
DINO
BLADE

10
LCD
Product
Series

11
Embedded
System

12
Industrial
Computer
Chassis

13
Power
Supply

14
Peripherals