


# RACK-2000G/2100G 2U 6-slot Full-size Rackmount Chassis



## Dimensions



## Features

- ◆ RoHS compliant design
- ◆ Stylish front panel with keylock
- ◆ One 5.25" and one 3.5" drive bay
- ◆ One 5.25" and one 3.5" drive bay
- ◆ Two 8 cm cooling fans with easy replaceable fan filter

## Specifications

◆ Construction	Heavy duty metal with plastic front panel
◆ SBC Form Factor	Full-size, slot CPU card
◆ Drive Bays	1 x front accessible 3.5" 1 x 3.5" HDD (internal) 1 x 5.25"
◆ Cooling Fans	2 x 8 cm
◆ Expansion Slots	6 slots
◆ Indicators	Power, HDD
◆ Buttons	Power switch, reset button
◆ Operating Temperature	0°C~50°C
◆ Operation Humidity	10% ~ 90%
◆ Color	W: White / B: Black
◆ Weight (Net/Gross)	7.8 kg / 11.8 kg
◆ Dimensions (DxWxH)	576.9 mm x 431 mm x 88 mm

## Selection Guide

Model No.	SBC Type	PSU Type	Color Options
RACK-2000G <span style="border: 1px solid black; padding: 0 2px;">C</span>	PICMG 1.0	PS/2	black / white
RACK-2000GBR	PICMG 1.0	redundant	black
RACK-2100G <span style="border: 1px solid black; padding: 0 2px;">C</span>	PICMG 1.3	PS/2	black / white
RACK-2100GBR	PICMG 1.3	redundant	black

## Backplane Options

Model No.	SBC Type	PCI	ISA	PCIe			PSU Connector
				x1	x4	x16	
PCI-5SDA-RS-R40 <sup>1</sup>	PICMG 1.0	L2+R2	0	0	0	0	AT/ATX
PCI-5SD5-RS-R40 <sup>1</sup>	PICMG 1.0	L2+R2	0	0	0	0	AT
PCI-6SD-RS-R40 <sup>1</sup>	PICMG 1.0	L1+R1	L1+R1	0	0	0	ATX
PE-6SD-R40 <sup>2</sup>	PICMG 1.3	0	0	3	0	1	ATX
PE-6SD2-R40 <sup>2</sup>	PICMG 1.3	1	0	2	0	1	ATX
PE-6SD3-RS-R40 <sup>2</sup>	PICMG 1.3	2	0	0	1	1	ATX

<sup>1</sup>Backplanes for RACK-2000G  
<sup>2</sup>Backplanes for RACK-2100G

## Ordering Information

Part No.	Description
RACK-2000G <span style="border: 1px solid black; padding: 0 2px;">C</span> /ACE-832AP	2U 6-slot full-size rackmount chassis for PICMG 1.0 SBC, with ACE-832AP-RS, RoHS
RACK-2000GBR /ACE-R4130AP	2U 6-slot full-size rackmount chassis for PICMG 1.0 SBC, black, with ACE-R4130AP-RS, RoHS
RACK-2100G <span style="border: 1px solid black; padding: 0 2px;">C</span> /ACE-832AP	2U 6-slot full-size rackmount chassis for PICMG 1.3 SBC, with ACE-832AP-RS, RoHS
RACK-2100GBR /ACE-R4130AP	2U 6-slot full-size rackmount chassis for PICMG 1.3 SBC, black, with ACE-R4130AP-RS, RoHS

C Color Code: B-Black W-White

## Power Supply Options

Type	Model No.	Watt
AT	ACE-925AP-U-RS	250W
	ACE-935AL-RS	300W
ATX	ACE-832AP-RS	300W
	ACE-841AP-S-RS	400W
ATX Redundant <sup>3</sup>	ACE-R4130AP-RS	300W
	ACE-R4140AP-RS	400W

<sup>3</sup> Only RACK-2000GBR and RACK-2100GBR can support ATX redundant power supply. For more models of IEI PSU, please visit [www.ieiworld.com](http://www.ieiworld.com).

1 Application Server Platform

2 Single Board Computer

3 IBX Series POS PC

4 AFOLUX POS Panel PC

5 Video Capture Card

6 KAMIO RISC

7 IOVU Open HMI

8 VITO Universal Controller

9 DINO BLADE

10 LCD Product Series

11 Embedded System

12 Industrial Computer Chassis

13 Power Supply

14 Peripherals